

## MPOSD



### Multipurpose Suction & Discharge Hose

# Part Number	Hose I.D.		Hose O.D.		Working Pressure		Minimum Bend Radius	
	inch	mm	inch	mm	psi	bar	inch	mm
MPOSD2WR4PM - 32PM	2.0	50.8	2.80	71.1	600	41	24.0	610
MPOSD2WR4PM - 48PM	3.0	76.2	3.80	96.5	600	41	36.0	914
MPOSD2WR4PM - 64PM	4.0	101.6	4.80	121.9	500	34	48.0	1219

#### Application:

- Brine, crude oil, mild chemicals, petroleum waste, sediments, sludge, slurries, water.
- Frac tank transfer, oil field waste recovery, general industrial.

Vacuum : Full

#### Construction:

Inner tube : NBR - Synthetic rubber  
 Reinforcement : Two braids steel wire with one helical wire  
 Outer Cover : SBR - Synthetic rubber

Design Factor : 4:1

#### Temp. Range

-40°C to +100°C  
 (-40°F to +212°F)

## SLIM HOLE ROTARY HOSE



### Oilfield Hose

# Part Number	Hose I.D.		Hose O.D.	Working Pressure		Minimum Bend Radius		Approx. Weight	
	inch	mm	mm	psi	bar	inch	mm	lbs/ft	kg/m
701PM-40PM	2-1/2	63.5	81.3	3000	207	30.0	762	—	—
701PM-48PM	3	76.2	96.0	3000	207	43.5	1105	4.50	6.70
701PM-64PM	4	101.6	125.0	2000	138	59.0	1500	5.94	8.85

#### Application:

- Off-shore applications and hydraulic drill rigs.
- Suitable for petroleum based hydraulic fluids, synthetic esters, biodegradable hydraulic fluids, water-glycol based fluids and air.

#### Construction:

Inner Tube : CR - Synthetic rubber  
 Reinforcement : Four steel wire spirals  
 Outer Cover : SBR - Synthetic rubber

#### Temp. Range

-40°C to + 121°C  
 (-40°F to +250°F)