



SUPER-FLEX®

EPDM Water Suction Hose

Series 7392E

Series 7392E is a lightweight suction and discharge hose designed to handle alkalis, brine, glycols, herbicides, mild chemicals, slurries and water. The hose construction incorporates a wire helix that provides full suction capability and kink resistance. The EPDM cover is resistant to abrasion, heat, mild chemicals and weathering.

| | |
|----------------------------|---|
| Tube: | Black EPDM |
| Reinforcement: | Multiple textile plies with wire helix |
| Cover: | Black EPDM; wrapped finish |
| Temp. Range: | -40°F to +180°F (-40°C to +82°C) |
| Brand Method: | White text on blue stripe |
| Brand Example: | PARKER SERIES 7392E WATER SUCTION HOSE – XXX PSI MAX WP |
| Industry Standards: | None applicable |
| Applications: | <ul style="list-style-type: none"> • Alkalis, brine, glycols, herbicides, mild chemicals, slurries, water • Agriculture, construction, general industrial, irrigation, surface mining |
| Vacuum: | Full |
| Compare to: | Gates Barracuda; Veyance Plicord Con-Ag Water S&D |
| Packaging: | Coils |

| Part Number | ID (in) | ID (mm) | Reinf Plies | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/ft) | Min Bend Rad (in) | Min Bend Rad (mm) | Max Rec WP (psi) | Max Rec WP (bar) | Perm Cplg Rec * | Std Pack Qty (ft) | Stock Status ** |
|-------------|---------|---------|-------------|---------|---------|--------------------|-------------------|-------------------|-------------------|------------------|------------------|-----------------|-------------------|-----------------|
| 7392E-1500 | 1-1/2 | 38.1 | 2 | 1.890 | 48.0 | 0.72 | 0.33 | 6.0 | 152.4 | 150 | 10.3 | * | 100 | Y |
| 7392E-2000 | 2 | 50.8 | 2 | 2.440 | 62.0 | 1.08 | 0.49 | 7.0 | 177.8 | 150 | 10.3 | * | 100 | Y |
| 7392E-2500 | 2-1/2 | 63.5 | 2 | 2.950 | 74.9 | 1.45 | 0.66 | 8.0 | 203.2 | 150 | 10.3 | * | 100 | Y |
| 7392E-3000 | 3 | 76.2 | 2 | 3.500 | 88.9 | 1.80 | 0.82 | 10.0 | 254.0 | 150 | 10.3 | * | 100 | Y |
| 7392E-4000 | 4 | 107.0 | 2 | 4.530 | 115.1 | 2.43 | 1.10 | 22.0 | 558.8 | 100 | 6.9 | * | 100 | Y |
| 7392E-6000 | 6 | 152.4 | 4 | 6.570 | 166.9 | 4.16 | 1.89 | 30.0 | 762.0 | 100 | 6.9 | * | 100 | Y |

* **Couplings:** Refer to CrimpSource at www.safehose.com for coupling recommendations and crimp specifications.

** **Stock:** “Y” indicates stocked item; “N” indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

⚠ WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. [Refer to the NAHAD Industrial Hose Assembly Guidelines.](#)



SUPER-FLEX®

EPDM Water Suction Hose

Series 7392E

Series 7392E is a lightweight suction and discharge hose designed to handle alkalis, brine, glycols, herbicides, mild chemicals, slurries and water. The hose construction incorporates a wire helix that provides full suction capability and kink resistance. The EPDM cover is resistant to abrasion, heat, mild chemicals and weathering.

| | |
|----------------------------|---|
| Tube: | Black EPDM |
| Reinforcement: | Multiple textile plies with wire helix |
| Cover: | Black EPDM; wrapped finish |
| Temp. Range: | -40°F to +180°F (-40°C to +82°C) |
| Brand Method: | White text on blue stripe |
| Brand Example: | PARKER SERIES 7392E WATER SUCTION HOSE – XXX PSI MAX WP |
| Industry Standards: | None applicable |
| Applications: | <ul style="list-style-type: none"> Alkalis, brine, glycols, herbicides, mild chemicals, slurries, water Agriculture, construction, general industrial, irrigation, surface mining |
| Vacuum: | Full |
| Compare to: | Gates Barracuda; Veyance Plicord Con-Ag Water S&D |
| Packaging: | Coils |

| Part Number | ID (in) | ID (mm) | Reinf Plies | OD (in) | OD (mm) | Approx Wt (lbs/ft) | Approx Wt (kg/ft) | Min Bend Rad (in) | Min Bend Rad (mm) | Max Rec WP (psi) | Max Rec WP (bar) | Perm Cplg Rec * | Std Pack Qty (ft) | Stock Status ** |
|-------------|---------|---------|-------------|---------|---------|--------------------|-------------------|-------------------|-------------------|------------------|------------------|-----------------|-------------------|-----------------|
| 7392E-1500 | 1-1/2 | 38.1 | 2 | 1.890 | 48.0 | 0.72 | 0.33 | 6.0 | 152.4 | 150 | 10.3 | * | 100 | Y |
| 7392E-2000 | 2 | 50.8 | 2 | 2.440 | 62.0 | 1.08 | 0.49 | 7.0 | 177.8 | 150 | 10.3 | * | 100 | Y |
| 7392E-2500 | 2-1/2 | 63.5 | 2 | 2.950 | 74.9 | 1.45 | 0.66 | 8.0 | 203.2 | 150 | 10.3 | * | 100 | Y |
| 7392E-3000 | 3 | 76.2 | 2 | 3.500 | 88.9 | 1.80 | 0.82 | 10.0 | 254.0 | 150 | 10.3 | * | 100 | Y |
| 7392E-4000 | 4 | 107.0 | 2 | 4.530 | 115.1 | 2.43 | 1.10 | 22.0 | 558.8 | 100 | 6.9 | * | 100 | Y |
| 7392E-6000 | 6 | 152.4 | 4 | 6.570 | 166.9 | 4.16 | 1.89 | 30.0 | 762.0 | 100 | 6.9 | * | 100 | Y |

* **Couplings:** Refer to CrimpSource at www.safehose.com for coupling recommendations and crimp specifications.

** **Stock:** “Y” indicates stocked item; “N” indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

⚠ WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. [Refer to the NAHAD Industrial Hose Assembly Guidelines.](#)